

CULTIVATORS



VIBROFLEX TILLER



Vibrating Effect



Enhanced Growth



Three-point Linkage

The vibroflex tiller series is mounted on the three-point linkage of the tractor. The optimum operating speed is 12 kilometers per hour for the necessary vibrating effect to ensure maximum efficiency. The vibroflex tiller is used for weeding, cultivation of soil and seedbed preparation. Advantages of the vibroflex include: soil can be worked and reconsolidated in one pass, optimum seedbed preparation, loosens top layer of soil to allow faster germination and enhanced plant growth.

STOCK CODE	AVBT 2 / 7	AVBT 2 / 9	AVBT 3 / 9	AVBT 3 / 11	AVBT 3 / 13	AVBT 3 / 15
FRAME	DOUBLE BEAM	DOUBLE BEAM	TRIPLE BEAM	TRIPLE BEAM	TRIPLE BEAM	TRIPLE BEAM
NUMBER OF TINES	7	9	9	11	13	15
TOTAL WIDTH	2 000mm	2 500mm	2 500mm	3 000mm	3 500mm	4 000mm
WORKING DEPTH	50 - 150mm	50 - 150mm	50 - 150mm	50 - 150mm	50 - 150mm	50 - 150mm
DEPTH CONTROL WHEELS	NO	NO	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
WORKING WIDTH	1 750mm	2 250mm	2 250mm	2 750mm	3 250mm	3 750mm
SPACE BETWEEN TINES	250mm (ADJUSTABLE)	250mm (ADJUSTABLE)	250mm (ADJUSTABLE)	250mm (ADJUSTABLE)	250mm (ADJUSTABLE)	250mm (ADJUSTABLE)
TINE LENGTH	650mm	650mm	650mm	650mm	650mm	650mm
REQUIRED POWER	40 - 45kW	55 - 60kW	50 - 60kW	70 - 75kW	85 - 90kW	95 - 100kW
ROLLER/CRUMBLER	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL

Manufacturer reserves the rights to change the above without any notice.