



The MASCAR Diavel is a fixed chamber round baler with rollers. The new design and high-level technical characteristics are enhanced for productivity and quality that is second to none. The transmission is distributed in a homogeneous way, on one side the pick up and on the other one the rollers, net and twine binder, which is easy and has low maintenance costs. The intuitive and ergonomic monitor allows having the control and the management of the round baler in a constant way.

CHAMBER	Fix
BALE DIAMETER	1 300mm
BALE WIDTH	1 200mm
NUMBER OF ROLLERS	18
PICK-UP WIDTH (DIN 112200)	2 000mm
TINES ROW/TINES FOR EACH ROW	4/28
TINE PITCH	65mm
CUTTING SYSTEM	15 (0-15)
DROP FLOOR	Standard
NET BINDING	Standard
DOUBLE TWINE BINDING	Optional
BALE EJECTOR	Optional
AUTOMATIC CHAINS LUBRICATION	Standard
CENTRALISED GREASING SYSTEM	Standard
SEMI-AUTOMATIC GREASING SYSTEM	Optional
STANDARD TYRES	15.0 55-77
OPTIONAL TYRES	500/50-17
POWER SUPPLY	12V-20A
HYDRAULIC TRACTOR REQUIREMENTS	2 x DE
HYDRAULIC BRAKES	Optional
PNEUMATIC BRAKES	Optional
ADJUSTABLE DRAWBAR	Adjustable
P.T.O. SHAFT	Wide angle cam type overload clutch
MINIMUM REQUIRED POWER	74kW/100hp
RPM FROM P.T.O.	540g/min
WIDTH WITH TYRES 15.0/55-17 (500/50-17)	2 380mm (2 600mm)
HEIGHT	2 340mm
LENGTH	4 340mm
EMPTY WEIGHT	3 270kg

