

# HARROWS



## ROTARY HARROW



**Loosens Soil**



**Tined Wheels**



**Three-point Linkage**

The Rotary Harrows are ideal for loosening hard crusted and compacted soil after heavy rains. This implement is mounted on the tractor's three-point linkage system. Models are available in single or tandem carts (per row). The single carts consist of four wheels with 16 tines per wheel and the tandem cart consist of four wheels in front and three wheels at the rear with 16 tines on each wheel. The 116 three-point mounted Rotary Harrow is utilised for harrowing directly on the row.

SINGLE AXLE					
STOCK CODE	000A116A01	000A116A02	000A116A03	000A116A04	000A116A10
MODEL SIZES	3-ROW x 1 500mm	3-ROW x 2 300mm	4-ROW x 900mm	6-ROW x 900mm	8-ROW x 900mm (Hydraulic)
CIRCLE PLATES PER UNIT	4	4	4	4	4
TINES PER CIRCLE PLATE	16	16	16	16	16
CIRCLE PLATE THICKNESS AND DIAMETER	4.5 x 279mm	4.5 x 279mm	4.5 x 279mm	4.5 x 279mm	4.5 x 279mm
REQUIRED POWER	55 - 64kW	55 - 64kW	55 - 64kW	55 - 64kW	55 - 64kW
TANDEM					
STOCK CODE	000A116A05	000A116A06	000A116A07	000A116A08	000A116A09
MODEL SIZES	3-ROW x 1 500mm	3-ROW x 2 300mm	4-ROW x 900mm	6-ROW x 900mm	8-ROW x 900mm (Hydraulic)
CIRCLE PLATES PER UNIT	7	7	7	7	7
TINES PER CIRCLE PLATE	16	16	16	16	16
CIRCLE PLATE THICKNESS AND DIAMETER	4.5 x 279mm	4.5 x 279mm	4.5 x 279mm	4.5 x 279mm	4.5 x 279mm
REQUIRED POWER	55 - 64kW	55 - 64kW	55 - 64kW	55 - 64kW	55 - 64kW

*Manufacturer reserves the rights to change the above without any notice.*