



Available also as platform version.

DEUTZ-FAHR  
AGROFARM 85-100-115 G



Technical data and pictures are guideline only. Whilst making every effort to meet your requirements, DEUTZ-FAHR may make changes at any time and is not required to give notice thereof.

TECHNICAL DATA		AGROFARM G		
		85	100	115
<b>ENGINE</b>				
Emissions		Tier1	Tier1	Tier2
Manufacturer		SDF 1000.4 W	SDF 1000.4 WT	SDF 1000.4 WT1
Cylinders/Capacity	No./cc	4/4,000	4/4,000	4/4,000
Naturally aspirated		●	-	-
Turbocharged intake		-	●	●
Turbo Intercooler intake		-	-	●
Max. homologated power (ECE R 120)	kW/hp	61/83	70.6/96	81/110
Max. engine speed (rated)	rpm	2350	2300	2350
Max. torque	Nm	257	342	396
Engine control mechanical		●	●	-
Engine control electronically		-	-	●
Cyclone prefilter		○	○	○
Cooling liquid		●	●	●
Under-hood silencer with vertical exhaust		●	●	●
Fuel tank capacity	litres	150	150	150
Biodiesel fuel	%	B100	B100	B100
<b>MECHANICAL GEARBOX</b>				
Synchromesh		●	●	●
Number of speeds	n°	15+15	15+15	15+15
Number of speeds with supercreeper gear		20+20	20+20	20+20
Minimum/maximum speed with supercreeper gear	km/h	1.85/0.20	2.01/0.22	2.01/0.22
Number of speeds with Hi-Lo	n°	30+30	30+30	30+30
Number of speeds with Hi-Lo and creeper	n°	40+40	40+40	40+40
Max. speed	km/h	40	40	40
Mechanical dry clutch, single		●	●	●
<b>REAR PTO</b>				
Multiplate wet clutch		●	●	●
Electrohydraulic control		●	●	●
PTO 540/1 000		●	●	●
PTO 540/540ECO/1000/1000ECO		○	○	○
Ground speed PTO		○	○	○
<b>FRONT AND REAR AXLE</b>				
Front wheel drive electrohydraulically engaged		●	●	●
Electrohydraulically operated differential lock		●	●	●
Steering angle 2WD	degrees	65°	65°	65°
Steering angle 4WD	degrees	50°	55°	55°
<b>BRAKES</b>				
Braking system with wet brake discs		●	●	●
Mechanical parking brake		●	●	●
<b>STEERING</b>				
Hydrostatic steering with independent pump		●	●	●
Steering pump delivery	l/min	33	41	41
<b>HITCH</b>				
Category		II	II	II
Rear hitch mechanical		●	●	●
Rear hitch lift capacity	kg	2,150	4,200	4,800
<b>HYDRAULIC SYSTEM</b>				
Pump output (std)	l/min	56	56	56
Open-centre hydraulic system		●	●	●
Mechanical distributor engagement		●	●	●
Rear auxiliary distributors	No. of ways	2/4/6/8	2/4/6/8	2/4/6/8
<b>DRIVING POSITION</b>				
Side control levers		●	●	●
Cab and/or ROPS		●	●	●
ROPS with sun shade		○	○	○
Driver seat with mechanical suspension		●	●	●
Instrumentation analogue		●	●	●
<b>DIMENSIONS AND WEIGHTS</b>				
Standard rear tyres		420/85R30"	420/85R30"	420/85R30"
Max. length	mm	3,850	3,850	3,990
Max. length with rear linkage	mm	4,060	4,150	4,150
Width (min-max)	mm	2,050-2,458	2,050-2,458	2,050-2,458
Wheelbase (4WD/2WD)	mm	2,310/2,290	2,310/2,290	2,340/2,320
Front track (min-max) 2WD	mm	1,600-2,100	1,600-2,100	1,600-2,100
Front track (min-max) 4WD	mm	1,630-2,030	1,630-2,030	1,630-2,030
Rear track (min-max)	mm	1,602-2,002	1,602-2,002	1,602-2,002
Max height at ROPS	mm	2,710	2,790	2,790
Max. height with cab	mm	2,740	2,790	2,790
Weight with ROPS (4WD/2WD)	kg	3,760/3,120	4,120/3,540	4,120/3,540
Weight with cab (4WD/2WD)	kg	4,100/3,260	4,460/3,680	4,660/3,680
Maximum load capacity (4WD/2WD)	kg	6100/4800	6100/4800	7200/5300

STD ● OPT ○ - Not available

Dealer



Use of original lubricants and coolants is recommended.

DEUTZ-FAHR is a brand of SDF  
deutz-fahr.com

