

Landini



2 SERIES 2-050

ENGINE

YANMAR

Type	4TNV88-KLN
Rated Power (ISO) kW	35
Rated speed (rpm)	2800
Max. Torque (Nm)	141
Max. Torque Speed (rpm)	1200
Bore/Stroke	88/90
Displacement/No of Cylinders (cm³)	2189/4
Water Cooling	STD
Air Filter	Dry
Tank Capacity (lt)	40

CLUTCH

Independent Dual Dry Clutch (inch)	9
Mechanical Engagement	STD

TRANSMISSION

Basic Gearbox + Reverse Shuttle 12Fwd + 12Rev	STD
Rear Mechanical Diff. Lock	STD

POWER TAKE OFF

Mechanical Engagement	STD
2 Speeds 540/750 (rpm)	STD
1" 3/8 PTO Shaft with 6 Splines	STD
Ground Speed	STD

4WD FRONT AXLE

Mechanical 4WD Engagement	STD
Max. steering angle 55°	STD

BRAKING SYSTEM

Mechanical	STD
Oil-bath Graphite Coated Rear Brakes - 6 Discs	STD

HYDRAULIC SYSTEM

Mechanical operated.	STD
Position, Draft, Intermix & Floating Control Functions	STD
Standard Lifting Capacity (kg)	1200
Hydraulic Pump Delivery, Hydraulic Lift/Steering (ltr/min)	28/20
3-Point Linkage, CAT I	STD
Auxiliary Hydraulic Valves Double Acting	2

TYRES, WHEELS & DIMENSIONS

Front Tyres	4WD	260/70 R16
Rear Tyres	4WD	320/70 R24
Total Length with Ballast	(mm)	3225
Max Ground Clearance	(mm)	385
Wheelbase 4WD	(mm)	1760
Height at Steering Wheel	(mm)	1312
Min Width	(mm)	1385
Height to Safety Frame	(mm)	2097
Weight without Ballast 4WD	(kg)	1460

TRACK

Front Track Adjustment 4WD (mm) #	1083-1314
Rear Track Adjustment (mm) #	872-1258

CONFIGURATION

Front Ballast Weights (kg)	4x24
----------------------------	------

STD = Standard - = Not Available **OPT** = Optional

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.

